



## HHC-HP254

HD ANALOG 1080P / 3D-DNR / D-WDR / TDN  
CMOS COLOR IR BULLET CAMERA

### FEATURES

- 1/3.2" 8Megapixel Samsung LSI CMOS
- 1080P AHD, TVI & CVBS Solution
- Min. Illumination of 0.0005Lux
- True Day & Night
- Defog(Visibility enhancement on the low contrast scene)
- 2D & 3D Digital Noise Reduction
- Motion Detection, Privacy Masking (4 Zone)
- 54pcs IR LED(50m)
- Fixed Lens 6mm
- IP66 Weatherproof
- Option : OSD Controller

### CAMERA SPECIFICATIONS

Signal Format	NTSC/PAL
Image Sensor	1/3.2" 8Mega pixel Samsung LSI CMOS
Effective Pixels	3264(H) x 2448(V)
Scanning System	Progressive Scan
Resolution	HD Analog : 1920 x1080p
	Analog : 1000TVL
Min. Illumination	Color : 0.1 lux/BW : 0.0051lux
	Color sense-up : 0.08 lux/BW sense-up : 0.0005 lux
Electronic Shutter Speed	AUTO / FLK
	NTSC : 1/30~1/60,000sec PAL : 1/25~1/50,000sec
S/N Ratio	More than 52dB (AGC off)
Backlight Compensation	BLC / HSBLC
White Balance	ATW / AWC-SET / INDOOR / OUTDOOR / MANUAL / AWB
2D + 3D DNR	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO / COLOR / BW / EXT
Sense-up	Auto(x6) / x2 / x4 / x6 / x8 / x10 / x15 / x20 / x25 / x30
D-WDR	ON / OFF
Motion Detection	ON / OFF
Privacy Masking	4 Zone
Defog	ON / OFF
D-EFFECT	OFF / MIRROR / V-FLIP / ROTATE & FREEZE
Communication	Coaxial Comm..
Lens	Fixed Lens 6mm
Power Supply	DC 12V ±30%
Power Consumption	Max. 8.5W
Operating Temperature	-10°C ~ +50°C (Humidity : 0%RH ~ 90%RH)
Dimension	81 (W) x 79(H) x 242.2(D)mm
Weight	Approx. 700g(W/Sunshield & Bracket)

### DIMENSION

