



## HHC-HP2H4VP

HD ANALOG 1080P / 3D-DNR / WDR / TDN  
CMOS COLOR IR BULLET CAMERA

### FEATURES

- 1/2.9" 2.1Megapixel SONY Exmor CMOS
- 1080P AHD, TVI, CVI & CVBS Solution  
Option : 1080P EX-SDI(HD-SDI)
- Min. Illumination of 0.001Lux(Sense-up x8)
- True Day & Night
- Defog(Visibility enhancement on the low contrast scene)
- 2D & 3D Digital Noise Reduction
- Motion Detection, Privacy Masking (4 Zone)
- High Power IR LED 4pcs(50m)
- Varifocal Lens 2.8~12.0mm
- IP66 Waterproof
- Option : OSD Controller

### CAMERA SPECIFICATIONS

Signal Format	NTSC/PAL
Image Sensor	1/2.9" 2.1Mega pixel SONY Exmor CMOS
Effective Pixels	1984(H) x 1092(V)
Scanning System	Progressive Scan
Resolution	1920 x1080p @ 30fps (CVBS : 1000TVL)
Min. Illumination	Color : 1.0 lux/BW : 0.5 lux Color sense-up : 0.001 lux (sense-up x8)
Electronic Shutter Speed	NTSC : 1/30~1/50,000sec PAL : 1/25~1/50,000sec
S/N Ratio	More than 50dB (AGC off)
Backlight Compensation	OFF / BLC / BLC / WDR
White Balance	ATW / AUTOEXT / PRESET / MANUAL
2D + 3D DNR	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO / COLOR / BW / EXT
Sense-up	x2 ~ x8
D-WDR	ON / OFF
Motion Detection	ON / OFF
Privacy Masking	16 Zone
Defog	ON / OFF
D-EFFECT	MIRROR / D-ZOOM / FLIP
Communication	Coaxial Comm..
Lens	Varifocal Lens 2.8~12.0mm
Power Supply	DC 12V ±30%
Power Consumption	Max. 10.2W
Operating Temperature	-10°C ~ +50°C (Humidity : 0%RH ~ 80%RH)
Dimension	85(W) x 118.5(H) x 217.3(D)mm
Weight	Approx. 750g(W/Sunshield & Bracket)

### DIMENSION

