



HHC-HP436

HD ANALOG 4M@30fps

CMOS COLOR IR BULLET CAMERA

FEATURES

- 1/3.2" 8Megapixel Samsung LSI CMOS
- 1440P AHD/TVI@30fps&960H CVBS Solution
- True Day & Night
- D-WDR
- 2D Digital Noise Reduction
- Lens Shading Correction, Mirror
- Built-in UTC Communication
- 36pcs IR LED(35m)
- Fixed Lens 3.6mm
- Option : OSD Controller
- IP66 Weatherproof

CAMERA SPECIFICATIONS

Signal Format	NTSC/PAL
Image Sensor	1/3.2" 8Mega pixel Samsung LSI CMOS
Effective Pixels	3264(H) x 2448(V)
Scanning System	Progressive Scan
Resolution	1440p@30fps (AHD/TVI) (CVBS : 960H)
Min. Illumination	Color : 0.5 lux/BW : 0.1 lux
Electronic Shutter Speed	NTSC : 1/30~1/50,000sec PAL : 1/25~1/50,000sec
S/N Ratio	More than 52dB (AGC off)
Backlight	OFF / BLC / HSBLC
White Balance	ATW / AWC -> SET
2D DNR	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO / COLOR / BW / EXT
Mirror	OFF / MIRROR / V-FLIP / ROTATE
D-WDR	ON / OFF
Sharpness	OFF / AUTO
LSC	OFF / ON
Smart IR	OFF / ON
DPC	Live DPC(OFF/ON) / White DPC222(OFF/ON)
Communication	UTC
Lens	Fixed lens f=3.6mm
Power Supply	DC 12V $\pm$ 30%
Power Consumption	Max. 6.3W
Operating Temperature	-10°C ~ +50°C (Humidity : 0%RH ~ 80%RH)
Dimension	66(W) x 64.5(H) x 198(D)mm
Weight	Approx. 650g(W/Sunshield & Bracket)

DIMENSION

