



2M X10 HD IP Indoor Mini PTZ Camera



Feature

- 2M X10 HD IP Indoor Mini PTZ Camera
- X120 Zoom Control(Optical X10 / Digital X12)
- MIN. Illuminance : 0.025 Lux(B/W) @ DSS On
- True Day & Night(ICR)
- BLC / WDR / De-Fog / Noise Reduction
- Image Stabilization
- 8 Privacy Masks with Spherical Coordinates
- Super Speed(360°/SEC.) with 360° Endless Pan Rotation
- The Shortest Path with Vector Drive Technology
- Micro Control(0.05°/SEC.) with Micro Stepping Control Technology
- 209 Presets / 10 Swings / 4 Patterns / 8 Groups
- 8 Scheduler Functions with RTC(Real Time Clock)
- CVBS Output
- RS-485 with Pelco-D Protocol
- 1 Sensor Input / 1 Sensor Output
- Audio Input & Output
- Memory Slot
- Vandalproof
- DC 12V

Dimension



Specification

Model		HIP-CZ10IC
Camera	Image Sensor	1/3" Panasonic CMOS Sensor
	Pixel	2,000K Pixels
	Zoom	Optical X10 / Digital X12
	Video Signal to Noise	More than 50 dB
	Focal Length	F1.6 ~ 1.8, f=5.1 ~ 51mm
	Angle of View	Horizontal : 54°(Wide) ~ 4.9°(Tele)
	MIN. Illuminance	0.5 Lux(Color) / 0.1 Lux(B/W) @ DSS Off 0.125 Lux(Color) / 0.025 Lux(B/W) @ DSS On
	Day & Night	Auto / Day / Night(ICR)
	Focus	Auto / Manual / Semi-Auto
	AE Mode	Auto / Iris / Shutter / Manual
	White Balance	Auto / Indoor / Outdoor / Manual(Red, Blue Gain Adjustable)
	BLC	On / Off
	WDR	On / Off
	De-Fog	On / Off
	Aperture	Adjustable
Pan/Tilt	Noise Reduction	Auto / Off / 1 ~ 3 Level
	Image Stabilization	On / Off
	Privacy Zone	8 Masks with Spherical Coordinate
	Range	Pan : 360°(Endless) / Tilt : 90° Preset : 360° / SEC.
	Pan/Tilt Speed	Manual : 0.05° ~ 360° / SEC.(Zoom Proportional)
		Swing : 10° ~ 180° / SEC.
	Preset	209 Presets
	Pattern	4 Patterns [768 Commands(Approximate 5 Minutes) / 1 Pattern]
	Swing	10 Swings
	Group	8 Groups
		(MAX. 40 Actions with The Combination of Preset, Pattern and Swing)
	Scheduler Function	8 Scheduler Functions with RTC(Real Time Clock)
	Other Functions	Auto Flip, Auto Parking, Power-up Action and Others
	Video Output	CVBS, 1.0 Vp-p
	RTC(Real Time Clock)	RTC Battery Backup Time : Approximate 2 Weeks
Physical	Communication	RS-485
	Protocol	Pelco-D
	OSD	English(Menu, Time, PTZ Information, Password Protection and Others)
	Sensor Input	1 Input, Photo-Coupler Type
	Alarm Output	1 Output, Relay Output, MAX. Load DC 24V / 1.0A or AC 125V / 0.5A
	Audio Input / Output	Mono, Line In / Out
	Network Interface	Ethernet 10/100 Base-T(RJ-45)
	Memory Slot	Micro SD
	Dimension	Dome : Ø125mm / Ø5.0"
		200(Ø) x 192.6(H) [mm] / 7.9(Ø) x 7.6(H) ["]
	Weight	1.6 kg / 3.6 lb
	Material	Dome : Poly Carbonate / Housing : ABS + Poly Carbonate
	Rated Power	DC 12V / 1.5A
	Operating TEMP.	0°C ~ 40°C / 32°F ~ 104°F

Specification & Design are subject to change without prior notice.

2M X10 HD IP Indoor Mini PTZ Camera



Specification


IP Part	
Video Compression	M-JPEG / H.264 Dual Streaming
Audio Compression	G.711 u-law, G.726 4 bits ADPCM
Resolution	MAX. Full HD(1080p30), 1920x1080, 1280x720, 640x352, 320x176
Compression Level	6 Levels (Low Compression / Highest / High / Normal / Low / Lowest)
Live Casting	Up to 30 FPS @ 1920x1080 Resolution
Audio Support	2 Way Live Audio
Transmission Control	VBR, CBR (32Kbps ~ 12Mbps)
Alarm Management	[Trigger] Video Loss / Video Recovered / Motion Detection / Sensor Input / Boot / Serial / Schedule and Others [Service] Image Buffering Service (8Mbytes Pre-Post Alarm Buffer), FTP/E-Mail Notification Service
Dynamic IP Support	Dedicated Dynamic IP Service using www.ipcctvdns.com
Security	Password Protection for Live, PTZ, Alarm Output and Audio
Software (IE)	Live-Cast and PTZ Control through Web Browser with Audio (MIN. PC Requirement : Windows XP, 2000, Vista / IE6.x or Higher / Pentium IV 1.6GHz or Higher)
CMS	Support Free 16 Channels, Full Featured PC NVR (MIN. PC Requirement : Windows XP, 2000 / Pentium IV 1.6GHz CPU or Higher / 256 Mbytes RAM or Higher / 64 Mbytes Video Memory or Higher)
Protocol	HTTP, TCP/UDP/IP, ARP, ICMP, RTP/RTSP, Multicast, Telnet, FTP, PPPoE, SMTP(E-Mail), DHCP, NTP, uPNP and Others ONVIF, PSIA Support
SDK	Open HTTP API, ActiveX for Live-Cast with Audio and PTZ
Installation & Maintenance	Configuration : Installation Wizard, HTTP, Telnet and Console Firmware Upgrade : HTTP, Telnet+FTP
Miscellaneous	Serial Input Data Transmission with Video, Different Time Zone Support, User-Wise Authentication Data and Time can be synchronized with an external NTP server, Live-Cast for up to 16 clients.

Specification & Design are subject to change without prior notice.


Feature

- High Image Quality with H.264
- H.264 & M-JPEG Dual Streaming
- Various Resolution Support
- Various Compression Level Support
- 30FPS @ 1920x1080
- 2 Way Live Audio
- Convenient Alarm Management
- Dynamic IP Support
- Various Network Protocol Support
- SDK Support
- ONVIF / PSIA Support

GUI



IP Finder



CMS